



Flush Speakers and Microphone

STS-S61-G / STS-S61-B
STS-M56-G / STS-M56-B

Our customer side speaker and omni-directional microphone set is mounted into a surface for a sleek look.

Physical Data

Dimensions	Height – 50mm (1.97") Width – 65mm (2.56") Depth – 120mm (4.72")
Weight	STS-S61: 413g (0.91lbs) STS-M56: 164g (0.36lbs)
Construction	Mild Steel Zintec Case
Finish	Grey Powder Coated Leatherette Black Textured Powder Coated

Technical Data

Speaker	RMS	5W
	Impedance	4Ω
	Output	SPL 1W @ 1M 85dB
	Frequency Response	150Hz - 10300Hz
Microphone	Directional Response	Omni-Directional
	Frequency Response	100Hz - 5000Hz
	Sensitivity	-42.5 ± 2.0dB @ 1KHz (0dB=1V/pa)
	Impedance	2K Ohms =/- @ 1KHz

Applications

For use where one to one communication takes place at a counter or booth with a security screen:

- Banks
- Post Offices
- Ticket Kiosks
- Information Centres
- Airports



Talk to us now:
+44 (0) 1732 223900 (UK & ROW)
+1 616 392 3400 (US & Canada)
www.contacta.co.uk