



## Half Bridge Bar Unit

STS-B94-LH-B / STS-B94-LH-G /  
STS-B94-RH-B / STS-B94-RH-G

Our combined speaker and directional microphone for counters with reduced space.

### Physical Data

Dimensions	Height – 240mm (9.44") Width – 280mm (11.02") Depth – 130mm (5.11")
Weight	757g (1.67lbs)
Construction	Mild Steel
Finish	Grey Powder Coated Leatherette
	Black Textured Powder Coated

### Technical Data

Speaker	RMS	5W
	Impedance	4Ω
	Output	SPL 1W @ 1M 85dB
	Frequency Response	150Hz - 11000Hz
Microphone	Directional Response	Cardioid
	Frequency Response	70Hz - 14000Hz
	Sensitivity	-67dB +/- 3dB @ 1kHz
	Impedance	1.6K Ohms +/- 30% @ 1KHz

### Applications

For use where one to one communication takes place at a counter or booth with a security screen:

- Banks
- Post Offices
- Ticket Kiosks
- Information Centres
- Airports

### Standards

- CE, ROHS and WEEE compliant



Talk to us now:  
+44 (0) 1732 223900 (UK & ROW)  
+1 616 392 3400 (US & Canada)  
[www.contacta.co.uk](http://www.contacta.co.uk)